

# Celocell 200 H

## Hydroxyethylcellulose - HEC

### Technical Data Sheet

#### *Characteristics*

Celocell 200 H, hydroxyethylcellulose gives powerful, stable thickening in both interior and exterior paints. A creamy in-can stability, excellent water resistance and a good rheology profile. At the same time Celocell 200 H, hydroxyethylcellulose serves as a protective colloid in emulsion polymerization.

#### *Applications*

Celocell 200 H, hydroxyethylcellulose products are widely used in latex paints, building materials, oilfield chemicals, cleaning and personal care products, and much more.

#### *Typical Properties*

Appearance	White to slightly off-white flowy powder
Moisture content (%)	≤ 6.0
Ash (%)	≥ 5
PH	6.0 - 8.5
Viscosity (mPa.s)	190.000-210.000
Density kg/m <sup>3</sup>	300~600
Particle Size	100 % Through 80 mesh

#### *Packaging*

25 Kg's multi layer paper - PE bag.

#### *Storage*

Store it in cool, dry place avoiding direct sunshine.

Warning : The information contained in this document is given in good faith and based on our current knowledge. It is only an indication and is in no way binding, particularly as regards of infringement or prejudice to third parties through the use of our products. We guarantee that our products comply with its sales specifications.